

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Cancelled)
2. (Currently Amended) The door hook of claim [[1]] 12 wherein the second distance is less than the first distance.
3. (Currently Amended) The door hook of claim [[1]] 12 also comprising double sided tape attached to at least one of the back side and spacer portion.
4. (Currently Amended) The door hook of claim [[1]] 12 wherein at least one of the front side and the back side is attached to the top member at an acute angle relative to the top member.
5. (Currently Amended) The door hook of claim [[1]] 12 wherein the U-shaped bracket is a molded body and the spacer position of the U-shaped bracket is molded adjacent the back side.
6. (Cancelled)

7. (Currently Amended) The door hook of claim ~~[[1]]~~ 12 wherein the U-shaped bracket is made of one of styrene, polycarbonate, polypropylene and a metal.

8. (Currently Amended) The door hook of claim ~~[[1]]~~ 12 wherein the top member is approximately 0.050 to 0.080 inches thick.

9. (Previously Presented) A door hook to be extended over a door top to both sides of a door, the door hook comprising a U-shaped bracket having:

a top member,

a front side which is attached to one edge of the top member, and

a back side which is attached to an other edge of the top member opposite the one edge, wherein the front side and back side are separated by a first distance;

a first hook member attached to the front side;

a spacer portion, the spacer portion being detachable from the U-shaped bracket and configured for reattachment to the back side such that the back side with the spacer portion reattached thereto and the front side are separated by a second distance between the front side and the spacer portion, the second distance being different from the first distance; and

a hook attached to the spacer portion.

10. (Currently Amended) The door hook of claim ~~[[1]]~~ 12 also comprising at least one of a locking member and an adhesive on one of the back side and the spacer portion which

locking member or adhesive is positioned to retain the spacer portion on the back side after that spacer portion has been reattached to the back side.

11. (Currently Amended) The door hook of claim ~~[[1]]~~ 9 further comprising a second hook member attached to the back side.

12. (Previously Presented) A door hook to be extended over a door top to both sides of a door, the door hook comprising a U-shaped bracket having:

a top member,

a front side which is attached to one edge of the top member, and

a back side which is attached to an other edge of the top member opposite the one edge, wherein the front side and back side are separated by a first distance;

a first hook member attached to the front side; and

a spacer portion, the spacer portion being detachable from the U-shaped bracket and configured for reattachment to the back side such that the back side with the spacer portion reattached thereto and the front side are separated by a second distance between the front side and the spacer portion, the second distance being different from the first distance;

wherein the spacer portion is connected to one of the top member, the front side and the back side by a frangible joint.

13. (Previously Presented) A door hook to be extended over a door top to both sides of a door, the door hook comprising a U-shaped bracket having:

a top member,  
a front side which is attached to one edge of the top member, and  
a back side which is attached to an other edge of the top member opposite the one edge, wherein the front side and back side are separated by a first distance;  
a first hook member attached to the front side; and  
a spacer portion, the spacer portion being detachable from the U-shaped bracket and configured for reattachment to the back side such that the back side with the spacer portion reattached thereto and the front side are separated by a second distance between the front side and the spacer portion, the second difference being different from the first distance;  
wherein the back portion and the spacer portion are plastic molded in a common plane and connected by a frangible joint.

14. (Currently Amended) The door hook of claim [[1]] 12 wherein the back side has a hole and a spacer portion further comprises a threaded portion which is positioned to fit into the hole and retain the spacer portion on the back side after that spacer portion has been reattached to the back side.

15. (Cancelled)

16. (Previously Presented) A door hook to be extended over a door top to both sides of a door, the door hook comprising a U-shaped bracket having:

a top member,

a front side which is attached to one edge of the top member, and  
a back side which is attached to an other edge of the top member opposite the one edge, wherein the front side and back side are separated by a first distance;  
a first hook member attached to the front side; and  
a spacer portion, the spacer portion being detachable from the U-shaped bracket and configured for reattachment to the back side such that the back side with the spacer portion reattached thereto and the front side are separated by a second distance between the front side and the spacer portion, the second distance being different from the first distance;  
wherein the spacer portion is connected to at least one of the back side and the top member by a frangible joint.

17. (Currently Amended) The door hook of claim ~~[[15]]~~ 16 wherein the U-shaped bracket is made of one of styrene, polycarbonate, polypropylene and metal.

18. (Currently Amended) The door hook of claim ~~[[15]]~~ 16 wherein the spacer portion is configured for reattachment to at least one of the top member, the front side and the back side.